

Technical Application Guide for UP-SHINE LED Downlight

UP-DL44-3-10W

Introduction



DL44 downlight is structural designed with integration of heatsink and surface cover, aims at increasing the heat dissipation area. IP54 waterproof for indoor use, especially for damp locations. UL94-V0 Fire-rated PC diffuser provides high light transmittance and even light output. It is an ideal replacement for residential and commercial lighting.

Up to 70% energy saving compared to standard CFL

Long lifetime of 40,000 hours

Dimmable when using triac dimmer

90° wide beam angle

90-95mm cutout

CCT: 3000K 4000K

5000K 5700K

No UV/IR light

Environment friendly, without Mercury or any other hazardous substances

Application notes

- IP54 for indoor use
- Professional electrician for installation only
- Switch off before installation
- Do not touch when in use
- Keep away from hot steam and corrosive gas

Application Areas

It is designed for general lighting applications in office, supermarket, shop, school, hotel, etc. It is also widely used for public areas, such as stairway, lobby, reception, corridors etc.


Certificate



RoHS



Product Information



Technical Specifications

Model	Voltage	Power	Power Factor	Lumen (±5%)	Beam angle	CCT	Lifespan	CRI	Dimmable	Dimension
UP-DL44-3-10W	AC100-240V	10W	≥0.9	730	90°	3000K	40000h	≥80	No	Ø104*31mm cutout 90-95mm
UP-DL44-3-10W	AC100-240V	10W	≥0.9	790	90°	4000K	40000h	≥80	No	Ø104*31mm cutout 90-95mm
UP-DL44-3-10W	AC100-240V	10W	≥0.9	770	90°	5000K	40000h	≥80	No	Ø104*31mm cutout 90-95mm
UP-DL44-3-10W	AC100-240V	10W	≥0.9	775	90°	5700K	40000h	≥80	No	Ø104*31mm cutout 90-95mm
UP-DL44-3-10W-D	AC230V	10W	≥0.9	650	90°	3000K	40000h	≥80	Yes	Ø104*31mm cutout 90-95mm
UP-DL44-3-10W-D	AC230V	10W	≥0.9	720	90°	4000K	40000h	≥80	Yes	Ø104*31mm cutout 90-95mm
UP-DL44-3-10W-D	AC230V	10W	≥0.9	700	90°	5000K	40000h	≥80	Yes	Ø104*31mm cutout 90-95mm
UP-DL44-3-10W-D	AC230V	10W	≥0.9	705	90°	5700K	40000h	≥80	Yes	Ø104*31mm cutout 90-95mm





Driver data Sheet

Driver data	DIM	Non-dim
Input rated Voltage	AC230V	AC100-240V
Frequency	50HZ	50/60HZ
Input Voltage	AC200-240V	AC85-265V
Efficiency	≥75%	≥85%
Total load Wattage	10W±1W	10W±1W
Power Factor	≥0.9	≥0.9
Rated input current	≤0.06A	≤0.12A
Full load output Voltage	DC39-46V	DC39-46V
Rated output current	240mA	260mA
Output current range	240mA±5%	260mA±5%
Power tolerance	±5%	±5%
Current output tolerance	±5%	±5%
Dimming range	8%-100%	—
Dimmer	Triac dimmers	—
Short circuit protection	PASS	PASS
Over voltage protection	PASS	PASS
Over temperature protection	PASS	PASS
Withstand voltage	AC3750V	AC3750V





Fixture Compatibility

Rated Wattage	Electrical Classification	Ingress Protection	Operating Temp	Operating Humidity	Storage Temp
10W	II	IP54	-20°C~45°C	0~90%	-20°C~65°C


Spectral Distribution



Photometric Diagram





Polar Diagram Comparison



AVERAGE BEAM ANGLE (50%): 92.5DEG




Driver lifetime & LED light decay rate





Temperature

- The testing is operated at 25°C
- The lifetime of capacitor, minimum of 5,000 hours if operated at 105°C, will be doubled whenever the temperature drops 10°C
- The highest withstand temperature of IC, MOS could be 120°C
- The highest withstand temperature of LED junction temperature is 150°C



Installation

Install requirements	
A-gap above the fitting	25mm
B-gap to the building material	25mm
C-gap to the thermal insulation	25mm



Packaging Information

	SIZE(CM)	N.W/pc (KGS)	G.W.(KGS)	Q'TY(PCS)
Carton	48.5 x 37 x 20	0.3	8.2	24

	CTNS	Q'TY(PCS)	VOLUME(CBM)
20" standard container	756	18144	28
40" standard container	1512	36288	56

